



Shell Helix *HX6 10W-40*

Synthetic technology motor oil - Helps to protect against sludge and wear

Shell Helix HX6 is an advanced formulation that enhances engine performance by helping to protect against engine sludge build-up and wear. It is suitable for a wide variety of vehicles for everyday driving conditions.

Proud Drivers Choose Shell Helix

Performance, Features & Benefits

- **Active cleansing technology**
Actively locks away harmful performance-robbing deposits.
- **Active clean-up**¹
Helps to remove sludge left behind by inferior oils.
- **Effective wear protection**²
Helps to extend engine life by protecting against wear.
- **Resistance to oil degradation**
Helps to maintain protection throughout the oil-drain interval.
- **Low-evaporation formulation**³
Low oil consumption for less frequent top-up.
- **Multi-fuel capability**
Can be used for gasoline, diesel and gas engines, and is also suitable for biodiesel and gasoline/ethanol blends.

¹ Based on a severe sludge clean-up test.

² Based on Sequence IVA engine test carried out at an independent laboratory.

³ Based on NOACK volatility test and equipment manufacturers' requirements.

Main Applications

- Shell Helix HX6 helps to prolong the engine life of modern vehicles in demanding daily driving conditions by protecting against wear. Shell Helix HX6 can be used for gasoline, diesel and gas engines, and it is also suitable for biodiesel and gasoline/ethanol blends.

Specifications, Approvals & Recommendations

- API SN/CF
- ACEA A3/B3, A3/B4
- MB-Approval 229.3
- VW 502.00/505.00
- Renault RN0700
- To find the right Shell Helix product for your vehicles and equipment, please consult Shell LubeMatch at: <http://lubematch.shell.com>
- Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical help desks.

Typical Physical Characteristics

Properties			Method	Shell Helix HX6
Viscosity Grade				10W-40
Kinematic Viscosity	@40°C	cSt	ASTM D445	93.75
Kinematic Viscosity	@100°C	cSt	ASTM D445	14.08
Viscosity Index			ASTM D2270	154
MRV	@-30°C	cP	ASTM D4684	17100
Density	@15°C	kg/m ³	ASTM D4052	854.2
Flash Point			ASTM D92	244
Pour Point			ASTM D97	-48

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

- **Health and Safety**

Shell Helix HX6 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.epc.shell.com/>

- **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.