



ASX 75W - 90

Shell Spirax S6 AXME 75W - 90

GL - 5

S6 AXME 75W - 90

가
(drive train)

가

S6 AXME 75W - 90

(OEM)

DESIGNED TO MEET CHALLENGES

&

&

- SAE J 2360 (PRI GL 0582)
- Volvo 97312
- MAN 342 Typ S1
- Meritor 076N, Meritor (EU) Extended Drain
- ZF 05B - 07A - 12B - 16F - 17B - 19C - 21B
- Scania STO 2:0G
- DAF
- Mack GO - J Plus
- API GL - 5, MT - 1
- US Military MIL - PRF - 2105E (Obsolete)
- Iveco Extended drain

가 가

(

(OEM)

가

Shell

LubaMatch

S6

AXME 75W - 90



(Transmission)

(Axle)

GL - 5/MT - 1

가

| Properties | | | Method | Shell Spirax S6 AXME 75W - 90 |
|-------------|----------|--------------------|-------------------------------|----------------------------------|
| SAE | | | SAE J 306 | 75W - 90 |
| | @40°C | mm ² /s | ISO 3104 | 115 |
| | @100°C | mm ² /s | ISO 3104 | 15.2 |
| Brook field | @ - 40°C | mPa s | ISO 9262 | 135000 |
| | @100°C | mm ² /s | CEC L - 45_A - 99 ISO 3104 | 14.5 |
| | | | ISO 2909 | 138 |
| | @15°C | kg/m ³ | ISO 12185 | 878 |
| (COC) | | °C | ISO 2592 | 210 |
| | | °C | ISO 3016 | - 42 |

S6 AXME 75W - 90

MSDS

MSDS <http://www.epc.shell.com/>



Bonhan

Koo