

Safety Data Sheet

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

Material Name : Shell Spirax S6 AXME 75W-90
Recommended Use / Restrictions of Use : Transmission oil.

Product Code : 001D8290

Supplier : **Shell Hong Kong Ltd**
35/F AIA Kowloon Tower, Landmark East
100 How Ming Street, Kwun Tong
Kowloon
Hong Kong

Telephone : (+852) 23231000
Fax : (+852) 24971437
Emergency Telephone Number : (+852) 2432 8704

Email Contact for Safety Data Sheet : If you have any enquiries about the content of this SDS please email lubricantSDS@shell.com

2. HAZARDS IDENTIFICATION

GHS Classification : Hazardous to the aquatic environment - Long-term Hazard, Category 3

GHS Label Elements

Symbol(s) :
No symbol

Signal Words : No signal word

Hazard Statement : **PHYSICAL HAZARDS:**
Not classified as a physical hazard under GHS criteria.

HEALTH HAZARDS:
Not classified as a health hazard under GHS criteria.

ENVIRONMENTAL HAZARDS:
H412: Harmful to aquatic life with long lasting effects.

GHS Precautionary Statements

Prevention : P273: Avoid release to the environment.

Response : No precautionary phrases.

Storage : No precautionary phrases.

Disposal: : P501: Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.

Safety Data Sheet

Other Hazards which do not result in classification : Not classified as flammable but will burn.

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture Description : Blend of severely hydrotreated slack wax, synthetic esters, polyolefins and additives. Highly refined mineral oil.

Classification of components according to GHS

Chemical Identity	Synonyms	CAS	Hazard Class (category)	Hazard Statement	Conc.
Alkyl phosphonate			Skin Corr., 2; Eye Dam., 1; Aquatic Chronic, 2;	H315; H318; H411;	0.10 - 0.90 %
Alkyl dithiophosphate			Eye Dam., 2; Aquatic Chronic, 1;	H319; H410;	0.25 - 0.90 %
Long-chain alkenyl amine			Acute Tox., 4; Skin Corr., 1A; Aquatic Acute, 1;	H302; H314; H400;	0.10 - 0.90 %
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *			Asp. Tox., 1;	H304;	0.00 - 90.00 %

Additional Information : The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346. The highly refined mineral oil is only present as additive diluent.

Refer to Ch 16 for full text of H phrases.

* contains one or more of the following CAS-numbers: 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69-9.

4. FIRST AID MEASURES

General Information : Not expected to be a health hazard when used under normal conditions.

The first aid measures for different exposure routes:

Inhalation : No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.

Skin Contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.

Safety Data Sheet

Eye Contact	:	Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.
Ingestion	:	In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Most Important Symptoms/Effects, Acute & Delayed	:	Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.
Immediate medical attention, special treatment	:	Treat symptomatically.

5. FIRE FIGHTING MEASURES

Clear fire area of all non-emergency personnel.

Specific hazards arising from Chemicals	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.
Suitable Extinguishing Media	:	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable Extinguishing Media	:	Do not use water in a jet.
Protective Equipment & Precautions for Fire Fighters	:	Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space.

6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe the relevant local and international regulations.

Personal Precautions, Protective Equipment and Emergency Procedures	:	Avoid contact with skin and eyes.
Environmental Precautions	:	Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
Methods and Material for Containment and Cleaning Up	:	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.
Additional Advice	:	Local authorities should be advised if significant spillages cannot be contained.

Safety Data Sheet

7. HANDLING AND STORAGE

- General Precautions** : Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
- Precautions for Safe Handling** : Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
- Conditions for Safe Storage** : Keep container tightly closed and in a cool, well-ventilated place. Use properly labelled and closeable containers. Store at ambient temperature.
- Product Transfer** : This material has the potential to be a static accumulator. Proper grounding and bonding procedures should be used during all bulk transfer operations.
- Recommended Materials** : For containers or container linings, use mild steel or high density polyethylene.
- Unsuitable Materials** : PVC.
- Other Advice** : Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

If the American Conference of Governmental Industrial Hygienists (ACGIH) value is provided on this document, it is provided for information only.

Occupational Exposure Limits

Material	Source	Type	ppm	mg/m3	Notation
Oil mist, mineral	ACGIH	TWA(Inhalable fraction.)		5 mg/m3	
	HK OEL	TWA(Mist.)		5 mg/m3	
	HK OEL	STEL(Mist.)		10 mg/m3	

- Additional Information** : Code of Practice on control of Air Impurities (Chemical Substances) in the Workplace issued under section 7A(1) of the Hong Kong FIUO should be referred.

Biological Exposure Index (BEI)

No biological limit allocated.

Safety Data Sheet

- Appropriate Engineering Controls** : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.
- Individual Protection Measures** : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.
- Respiratory Protection** : No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point >65°C(149 °F)].
- Hand Protection** : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash

Safety Data Sheet

	protection we recommend the same, but recognise that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time may be acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material.
Eye Protection	: Wear safety glasses or full face shield if splashes are likely to occur.
Protective Clothing	: Skin protection not ordinarily required beyond standard issue work clothes.
Thermal Hazards	: Not applicable.
Monitoring Methods	: Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory. Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.
	National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/ Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/ Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/ Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany. http://www.dguv.de/inhalt/index.jsp L'Institut National de Recherche et de Sécurité, (INRS), France http://www.inrs.fr/accueil
Environmental Exposure Controls	: Take appropriate measures to fulfil the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Amber. Liquid at room temperature.
Odour	: Slight hydrocarbon
Odour threshold	: Data not available
pH	: Not applicable.
Initial Boiling Point and	: > 280 °C / 536 °F estimated value(s)

Safety Data Sheet

Boiling Range	
Pour point	: Typical -42 °C / -44 °F
Flash point	: Typical 210 °C / 410 °F (COC)
Upper / lower	: Typical 1 - 10 %(V)
Flammability or Explosion limits	
Auto-ignition temperature	: > 320 °C / 608 °F
Vapour pressure	: < 0.5 Pa at 20 °C / 68 °F (estimated value(s))
Relative Density	: Typical 0.878 at 15 °C / 59 °F
Density	: Typical 878 kg/m ³ at 15 °C / 59 °F
Water solubility	: Negligible.
Solubility in other solvents	: Data not available
n-octanol/water partition coefficient (log Pow)	: > 6 (based on information on similar products)
Dynamic viscosity	: Data not available
Kinematic viscosity	: Typical 115 mm ² /s at 40 °C / 104 °F
Vapour density (air=1)	: > 1 (estimated value(s))
Electrical conductivity	: This material is not expected to be a static accumulator.
Evaporation rate (nBuAc=1)	: Data not available
Decomposition Temperature	: Data not available
Flammability	: Data not available

10. STABILITY AND REACTIVITY

Chemical stability	: Stable.
Possibility of Hazardous Reactions	: Reacts with strong oxidising agents.
Conditions to Avoid	: Extremes of temperature and direct sunlight.
Incompatible Materials	: Strong oxidising agents.
Hazardous Decomposition Products	: Hazardous decomposition products are not expected to form during normal storage.

11. TOXICOLOGICAL INFORMATION**Information on Toxicological effects**

Basis for Assessment	: Information given is based on data on the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Likely Routes of Exposure	: Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Acute Oral Toxicity	: Expected to be of low toxicity: LD50 > 5000 mg/kg , Rat
Acute Dermal Toxicity	: Expected to be of low toxicity: LD50 > 5000 mg/kg , Rabbit
Acute Inhalation Toxicity	: Not considered to be an inhalation hazard under normal conditions of use. Low toxicity by inhalation.

Safety Data Sheet

- Skin corrosion/irritation** : Expected to be slightly irritating. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.
- Serious eye damage/irritation** : Expected to be slightly irritating.
- Respiratory Irritation** : Inhalation of vapours or mists may cause irritation.
- Respiratory or skin sensitisation** : Not expected to be a skin sensitiser.
- Aspiration Hazard** : Not considered an aspiration hazard.
- Germ cell mutagenicity** : Not considered a mutagenic hazard.
- Carcinogenicity** : Not expected to be carcinogenic.

Material	Carcinogenicity Classification
Highly refined mineral oil (IP346 <3%)	ACGIH Group A4: Not classifiable as a human carcinogen.
Highly refined mineral oil (IP346 <3%)	IARC 3: Not classifiable as to carcinogenicity to humans.
Highly refined mineral oil (IP346 <3%)	GHS / CLP: No carcinogenicity classification

- Reproductive and Developmental Toxicity** : Not expected to be a hazard.
- Specific target organ toxicity - single exposure** : Not expected to be a hazard.
- Specific target organ toxicity - repeated exposure** : Not expected to be a hazard.
- Additional Information** : Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible.

12. ECOLOGICAL INFORMATION

- Basis for Assessment** : Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

- Ecotoxicity:**
- Acute Toxicity** : Poorly soluble mixture. May cause physical fouling of aquatic

Safety Data Sheet

	organisms. Expected to be harmful: LL/EL/IL50 10-100 mg/l (to aquatic organisms) LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract.
Microorganisms	: Data not available
Mobility	: Liquid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile. Floats on water.
Persistence/degradability	: Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.
Bioaccumulative Potential	: Contains components with the potential to bioaccumulate.
Other Adverse Effects	: Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.

13. DISPOSAL CONSIDERATIONS

Material Disposal	: Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses.
Container Disposal	: Dispose in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.
Local Legislation	: Disposal should be in accordance with applicable regional, national, and local laws and regulations.

14. TRANSPORT INFORMATION**Land (as per ADR classification): Not regulated**

This material is not classified as dangerous under ADR regulations.

IMDG

This material is not classified as dangerous under IMDG regulations.

IATA (Country variations may apply)

This material is either not classified as dangerous under IATA regulations or needs to follow country specific requirements.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution Category	: Not applicable.
Ship Type	: Not applicable.
Product Name	: Not applicable.
Special Precaution	: Not applicable.

Additional Information : MARPOL Annex 1 rules apply for bulk shipments by sea.

Safety Data Sheet

15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Chemical Inventory Status

EINECS : All components listed or polymer exempt.
TSCA : All components listed.

Other Information : Hong Kong Dangerous Goods Ordinance (CAP. 295) - Dangerous Goods (General) Regulations. Hong Kong Factories and Industrial Undertakings Ordinance (CAP. 59) - Factories and Industrial Undertakings (Dangerous Substances) Regulations. Hong Kong Waste Disposal Ordinance (CAP. 354) Section 35 - Code of Practice on the Packaging, Labelling and Storage of chemical Wastes.

16. OTHER INFORMATION

Hazard Statement

H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

SDS Version Number : 1.1
SDS Effective Date : 2013/06/06
SDS Revisions : A vertical bar (|) in the left margin indicates an amendment from the previous version.
SDS Distribution : The information in this document should be made available to all who may handle the product.
Disclaimer : This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property

Safety Data Sheet

of the product.