

Safety Data Sheet
Regulation 1907/2006/EC
Shell Gadus S2 V220AC 2

Version 2.1

Revision Date 08.07.2015

Print Date 09.07.2015

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product name : Shell Gadus S2 V220AC 2

Product code : 001D8456

Manufacturer or supplier's details

Manufacturer/Supplier : **Viva Energy Australia Ltd**
(Formerly: The Shell Company of Australia)
(ABN 46 004 610 459)
720 Bourke Street
Docklands
Victoria 3008
Australia

Telephone : +61 (0)3 8823 4444

Telefax : +61 (0)3 8823 4800

Emergency telephone number : 1800 651 818 (Australia).
POISONS INFORMATION CENTRE: 13 11 26 (Australia).

Recommended use of the chemical and restrictions on use

Recommended use : Automotive and industrial grease.

2. HAZARDS IDENTIFICATION

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS.

Not classified as hazardous according to the criteria of NOHSC, and not classified as Dangerous Goods according to the Australian Dangerous Goods Code.

Not a hazardous substance or mixture.

Label elements

Hazard pictograms : No Hazard Symbol required

Signal word : No signal word

Hazard statements : **PHYSICAL HAZARDS:**
Not classified as a physical hazard according to CLP criteria.
HEALTH HAZARDS:
Not classified as a health hazard under CLP criteria.
ENVIRONMENTAL HAZARDS:
Not classified as environmental hazard according to CLP criteria.

Precautionary statements : **Prevention:**
No precautionary phrases.
Response:
No precautionary phrases.
Storage:

Safety Data Sheet
Regulation 1907/2006/EC
Shell Gadus S2 V220AC 2

Version 2.1

Revision Date 08.07.2015

Print Date 09.07.2015

No precautionary phrases.

Disposal:

No precautionary phrases.

Other hazards

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used grease may contain harmful impurities. High-pressure injection under the skin may cause serious damage including local necrosis. Not classified as flammable but will burn.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : A lubricating grease containing highly-refined mineral oils and additives.
The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.

Hazardous components

4. FIRST-AID MEASURES

General advice : Not expected to be a health hazard when used under normal conditions.

If inhaled : No treatment necessary under normal conditions of use.
If symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.
If persistent irritation occurs, obtain medical attention.

When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop.
Obtain medical attention even in the absence of apparent wounds.

In case of eye contact : Flush eye with copious quantities of water.
If persistent irritation occurs, obtain medical attention.

If swallowed : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.

Most important symptoms and effects, both acute and delayed : Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas.
Ingestion may result in nausea, vomiting and/or diarrhoea.

Local necrosis is evidenced by delayed onset of pain and

Safety Data Sheet
Regulation 1907/2006/EC
Shell Gadus S2 V220AC 2

Version 2.1

Revision Date 08.07.2015

Print Date 09.07.2015

tissue damage a few hours following injection.

Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.

Notes to physician : Treat symptomatically.

High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function.

Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use water in a jet.

Specific hazards during firefighting : Hazardous combustion products may include:
A complex mixture of airborne solid and liquid particulates and gases (smoke).
Carbon monoxide may be evolved if incomplete combustion occurs.
Unidentified organic and inorganic compounds.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Avoid contact with skin and eyes.

Safety Data Sheet
Regulation 1907/2006/EC
Shell Gadus S2 V220AC 2

Version 2.1

Revision Date 08.07.2015

Print Date 09.07.2015

- Environmental precautions : Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
- Methods and materials for containment and cleaning up : Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers.
- Additional advice : For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet.
For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

7. HANDLING AND STORAGE

- General Precautions : Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
- Advice on safe handling : Avoid prolonged or repeated contact with skin.
Avoid inhaling vapour and/or mists.
When handling product in drums, safety footwear should be worn and proper handling equipment should be used.
Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
- Avoidance of contact : Strong oxidising agents.

Storage

- Other data : Keep container tightly closed and in a cool, well-ventilated place.
Use properly labeled and closable containers.

Store at ambient temperature.
- Packaging material : Suitable material: For containers or container linings, use mild steel or high density polyethylene.
Unsuitable material: PVC.
- Container Advice : Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of	Control parameters /	Basis
------------	---------	------------------------	-------------------------	-------

Safety Data Sheet

Regulation 1907/2006/EC

Shell Gadus S2 V220AC 2

Version 2.1

Revision Date 08.07.2015

Print Date 09.07.2015

		exposure)	Permissible concentration	
Oil mist, mineral	Not Assigned	TWA ((inhalable fraction))	5 mg/m ³	US. ACGIH Threshold Limit Values
		TWA (Mist)	5 mg/m ³	Australia. Workplace Exposure Standards for Airborne Contaminants.

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods
<http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods
<http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances
<http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany
<http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

Engineering measures

: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:
Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Due to the product's semi-solid consistency, generation of mists and dusts is unlikely to occur.

Personal protective equipment

Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection : No respiratory protection is ordinarily required under normal conditions of use.
In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for the combination of organic gases and vapours [Type A/Type P boiling point >65°C (149°F)].

Hand protection
Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is

Safety Data Sheet

Regulation 1907/2006/EC

Shell Gadus S2 V220AC 2

Version 2.1

Revision Date 08.07.2015

Print Date 09.07.2015

dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

- Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.
- Skin and body protection : Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical resistant gloves.
- Thermal hazards : Not applicable

Environmental exposure controls

- General advice : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Semi-solid at ambient temperature.
- Colour : red
- Odour : Slight hydrocarbon
- Odour Threshold : Data not available
- pH : Not applicable
- Drop point : 175 °C / 347 °F Method: IP 396
- Initial boiling point and boiling range : Data not available
- Flash point : ≥ 180 °C / ≥ 356 °F Method: ASTM D92
- Evaporation rate : Data not available
- Flammability (solid, gas) : Data not available
- Upper explosion limit : Typical 10 %(V)
- Lower explosion limit : Typical 1 %(V)
- Vapour pressure : < 0.5 Pa (20 °C / 68 °F)

Safety Data Sheet

Regulation 1907/2006/EC

Shell Gadus S2 V220AC 2

Version 2.1

Revision Date 08.07.2015

Print Date 09.07.2015

	estimated value(s)
Relative vapour density	: > 1 estimated value(s)
Relative density	: 0.900 (15 °C / 59 °F)
Density	: 900 kg/m ³ (15.0 °C / 59.0 °F) Method: Unspecified
Solubility(ies)	
Water solubility	: negligible
Solubility in other solvents	: Data not available
Partition coefficient: n-octanol/water	: Pow: > 6 (based on information on similar products)
Auto-ignition temperature	: > 320 °C / 608 °F
Viscosity	
Viscosity, dynamic	: Data not available
Viscosity, kinematic	: 220 mm ² /s (40.0 °C / 104.0 °F) Method: ASTM D445
	18 mm ² /s (100 °C / 212 °F) Method: ASTM D445
Conductivity	: This material is not expected to be a static accumulator.
Decomposition temperature	: Data not available

10. STABILITY AND REACTIVITY

Chemical stability	: Stable.
Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: Hazardous decomposition products are not expected to form during normal storage.

11. TOXICOLOGICAL INFORMATION

Safety Data Sheet
Regulation 1907/2006/EC
Shell Gadus S2 V220AC 2

Version 2.1

Revision Date 08.07.2015

Print Date 09.07.2015

Basis for assessment : Information given is based on data on the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Exposure routes : Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity : LD50 rat: > 5,000 mg/kg
Remarks: Expected to be of low toxicity:

Acute inhalation toxicity : Remarks: Not considered to be an inhalation hazard under normal conditions of use.

Acute dermal toxicity : LD50 Rabbit: > 5,000 mg/kg
Remarks: Expected to be of low toxicity:

Skin corrosion/irritation

Product:

Remarks: Expected to be slightly irritating., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Serious eye damage/eye irritation

Product:

Remarks: Expected to be slightly irritating.

Respiratory or skin sensitisation

Product:

Remarks: Not expected to be a skin sensitiser.

Chronic toxicity

Germ cell mutagenicity

Product:

Remarks: Not considered a mutagenic hazard.

Carcinogenicity

Product:

Remarks: Not expected to be carcinogenic.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skin-painting studies., Highly refined mineral oils are not classified as carcinogenic by the

Safety Data Sheet
Regulation 1907/2006/EC
Shell Gadus S2 V220AC 2

Version 2.1

Revision Date 08.07.2015

Print Date 09.07.2015

International Agency for Research on Cancer (IARC).

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

Other Carcinogenicity Classification:

Reproductive toxicity

Product:

Remarks: Not expected to impair fertility., Not expected to be a developmental toxicant.

STOT - single exposure

Product:

Remarks: Not expected to be a hazard.

STOT - repeated exposure

Product:

Remarks: Not expected to be a hazard.

Aspiration toxicity

Product:

Not considered an aspiration hazard.

Further information

Product:

Remarks: Used grease may contain harmful impurities that have accumulated during use. The concentration of such harmful impurities will depend on use and they may present risks to health and the environment on disposal., ALL used grease should be handled with caution and skin contact avoided as far as possible.

Remarks: High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Remarks: Slightly irritating to respiratory system.

12. ECOLOGICAL INFORMATION

Basis for assessment : Ecotoxicological data have not been determined specifically for this product.
Information given is based on a knowledge of the components

Safety Data Sheet

Regulation 1907/2006/EC

Shell Gadus S2 V220AC 2

Version 2.1

Revision Date 08.07.2015

Print Date 09.07.2015

and the ecotoxicology of similar products.
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s). (LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).

Ecotoxicity

Product:

- Toxicity to fish (Acute toxicity) : Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l
- Toxicity to crustacean (Acute toxicity) : Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l
- Toxicity to algae/aquatic plants (Acute toxicity) : Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l
- Toxicity to fish (Chronic toxicity) : Remarks: Data not available
- Toxicity to crustacean (Chronic toxicity) : Remarks: Data not available
- Toxicity to microorganisms (Acute toxicity) : Remarks: Data not available

Persistence and degradability

Product:

- Biodegradability : Remarks: Expected to be not readily biodegradable., Major constituents are expected to be inherently biodegradable, but contains components that may persist in the environment.

Bioaccumulative potential

Product:

- Bioaccumulation : Remarks: Contains components with the potential to bioaccumulate.
- Partition coefficient: n-octanol/water : Pow: > 6Remarks: (based on information on similar products)

Mobility in soil

Product:

- Mobility : Remarks: Semi-solid under most environmental conditions., If it enters soil, it will adsorb to soil particles and will not be mobile.
Remarks: Floats on water.

Other adverse effects

no data available

Product:

Safety Data Sheet
Regulation 1907/2006/EC
Shell Gadus S2 V220AC 2

Version 2.1

Revision Date 08.07.2015

Print Date 09.07.2015

Additional ecological information : Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities., Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.
Poorly soluble mixture., May cause physical fouling of aquatic organisms.
Mineral oil is not expected to cause any chronic effects to aquatic organisms at concentrations less than 1 mg/l.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Recover or recycle if possible.
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
Do not dispose into the environment, in drains or in water courses

Contaminated packaging : Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.
Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local legislation
Remarks : Disposal should be in accordance with applicable regional, national, and local laws and regulations.

14. TRANSPORT INFORMATION

National Regulations

ADG
Not regulated as a dangerous good

International Regulation

IATA-DGR
Not regulated as a dangerous good

IMDG-Code
Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category : Not applicable
Ship type : Not applicable
Product name : Not applicable
Special precautions : Not applicable

Safety Data Sheet
Regulation 1907/2006/EC
Shell Gadus S2 V220AC 2

Version 2.1

Revision Date 08.07.2015

Print Date 09.07.2015

Special precautions for user

Remarks : Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

Additional Information : MARPOL Annex 1 rules apply for bulk shipments by sea.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

R-phrases : Not classified.

S-phrases : Not classified.

Standard for the Uniform Scheduling of Medicines and Poisons : No poison schedule number allocated

National Code of Practice for the Preparation of Material Safety Data Sheets [NOHSC:2011] List of Designated Hazardous Substances [NOHSC:10005]. Approved Criteria for Classifying Hazardous Substances [NOHSC:1008]. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003]. Australian Dangerous Goods Code. Standard for the Uniform Scheduling of Medicines and Poisons.

Other international regulations

The components of this product are reported in the following inventories:

EINECS : All components listed or polymer exempt.

TSCA : All components listed.

AICS : All components listed.

16. OTHER INFORMATION

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

SDS Regulation : Regulation 1907/2006/EC

Further information

Other information : A vertical bar (|) in the left margin indicates an amendment from the previous version.

Safety Data Sheet

Regulation 1907/2006/EC

Shell Gadus S2 V220AC 2

Version 2.1

Revision Date 08.07.2015

Print Date 09.07.2015

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.