

# Safety Data Sheet

## Shell Spirax S6 AXME 80W-140

Version 2.3

Revision Date 10.08.2016

Print Date 11.08.2016

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Shell Spirax S6 AXME 80W-140

Product code : 001D8292

#### Manufacturer or supplier's details

Supplier : Viva Energy Australia Pty Ltd  
(Formerly: The Shell Company of Australia)  
(ABN 46 004 610 459)  
720 Bourke Street  
Docklands  
Victoria 3008  
Australia

Telephone : +61 (0)3 8823 4444 ;

Telefax : +61 (0)3 8823 4800

Emergency telephone number : 1800 651 818 (Australia). POISONS INFORMATION CENTRE: 13 11 26 (Australia).

#### Recommended use of the chemical and restrictions on use

Recommended use : Transmission oil.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Chronic aquatic toxicity : Category 3

#### GHS label elements

Hazard pictograms : No Hazard Symbol required

Signal word : No signal word

Hazard statements : PHYSICAL HAZARDS:  
Not classified as a physical hazard under GHS criteria.  
HEALTH HAZARDS:  
Not classified as a health hazard under GHS criteria.  
ENVIRONMENTAL HAZARDS:  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements :  
**Prevention:**  
P273 Avoid release to the environment.

**Response:**  
No precautionary phrases.

**Storage:**  
No precautionary phrases.

**Disposal:**

# Safety Data Sheet

## Shell Spirax S6 AXME 80W-140

Version 2.3

Revision Date 10.08.2016

Print Date 11.08.2016

P501 Dispose of contents/ container to an approved waste disposal plant.

Sensitising components : Contains N-phenyl-1-naphthylamine. May produce an allergic reaction.

### Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities. Not classified as flammable but will burn.

---

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Synthetic base oil and additives.

#### Hazardous components

| Chemical name            | CAS-No. | Classification  | Concentration [%] |
|--------------------------|---------|---|-------------------|
| N-phenyl-1-naphthylamine | 90-30-2 | Acute Tox.4; H302<br>Skin Sens.1B; H317<br>STOT RE2; H373<br>Aquatic Acute1;<br>H400<br>Aquatic Chronic1;<br>H410 | 0.25 - 0.9        |

For explanation of abbreviations see section 16.

---

### SECTION 4. FIRST-AID MEASURES

General advice : Not expected to be a health hazard when used under normal conditions.

If inhaled : No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.

In case of eye contact : Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.

If swallowed : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.

Most important symptoms and effects, both acute and delayed : Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.

# Safety Data Sheet

## Shell Spirax S6 AXME 80W-140

Version 2.3

Revision Date 10.08.2016

Print Date 11.08.2016

Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.

Notes to physician : Treat symptomatically.

---

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use water in a jet.

Specific hazards during firefighting : Hazardous combustion products may include:  
A complex mixture of airborne solid and liquid particulates and gases (smoke).  
Carbon monoxide may be evolved if incomplete combustion occurs.  
Unidentified organic and inorganic compounds.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

Hazchem Code : NONE

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Avoid contact with skin and eyes.

Environmental precautions : Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.

Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material.  
Reclaim liquid directly or in an absorbent.  
Soak up residue with an absorbent such as clay, sand or other

# Safety Data Sheet

## Shell Spirax S6 AXME 80W-140

Version 2.3

Revision Date 10.08.2016

Print Date 11.08.2016

suitable material and dispose of properly.

Additional advice : For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet.  
For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

---

### SECTION 7. HANDLING AND STORAGE

General Precautions : Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.  
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Advice on safe handling : Avoid prolonged or repeated contact with skin.  
Avoid inhaling vapour and/or mists.  
When handling product in drums, safety footwear should be worn and proper handling equipment should be used.  
Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.

Avoidance of contact : Strong oxidising agents.

Product Transfer : This material has the potential to be a static accumulator.  
Proper grounding and bonding procedures should be used during all bulk transfer operations.

#### Storage

Other data : Keep container tightly closed and in a cool, well-ventilated place.  
Use properly labeled and closable containers.  
  
Store at ambient temperature.

Packaging material : Suitable material: For containers or container linings, use mild steel or high density polyethylene.  
Unsuitable material: PVC.

Container Advice : Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

---

### SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### Components with workplace control parameters

#### Biological occupational exposure limits

No biological limit allocated.

# Safety Data Sheet

## Shell Spirax S6 AXME 80W-140

Version 2.3

Revision Date 10.08.2016

Print Date 11.08.2016

### Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods  
<http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods  
<http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances  
<http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany  
<http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

### Engineering measures

: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:  
Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

#### General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.

Practice good housekeeping.

### Personal protective equipment

#### Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection : No respiratory protection is ordinarily required under normal

# Safety Data Sheet

## Shell Spirax S6 AXME 80W-140

Version 2.3

Revision Date 10.08.2016

Print Date 11.08.2016

conditions of use.

In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for the combination of organic gases and vapours [Type A/Type P boiling point >65°C (149°F)].

Hand protection  
Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

Eye protection

: If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

Skin and body protection

: Skin protection is not ordinarily required beyond standard work clothes.  
It is good practice to wear chemical resistant gloves.

Thermal hazards

: Not applicable

### Environmental exposure controls

General advice

: Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in

# Safety Data Sheet

## Shell Spirax S6 AXME 80W-140

Version 2.3

Revision Date 10.08.2016

Print Date 11.08.2016

Chapter 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water.

Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

|   |   |
|---|---|
| Appearance                              | : Liquid at room temperature.   |
| Colour                                  | : amber   |
| Odour                                   | : Slight hydrocarbon  |
| Odour Threshold                         | : Data not available  |
| pH                                      | : Not applicable  |
| pour point                              | : $\leq -40$ °C / $\leq -40$ °F Method: ASTM D97                          |
| Melting / freezing point                | : Data not available  |
| Initial boiling point and boiling range | : $> 280$ °C / $536$ °F estimated value(s)                                |
| Flash point                             | : $201$ °C / $394$ °F<br>Method: ASTM D92                                 |
| Evaporation rate                        | : Data not available  |
| Flammability (solid, gas)               | : Data not available  |
| Upper explosion limit                   | : Typical 10 %(V)   |
| Lower explosion limit                   | : Typical 1 %(V)  |
| Vapour pressure                         | : $< 0.5$ Pa ( $20$ °C / $68$ °F)<br>estimated value(s)                   |
| Relative vapour density                 | : $> 1$ estimated value(s)  |
| Relative density                        | : $0.912$ ( $15$ °C / $59$ °F)  |
| Density                                 | : $912$ kg/m <sup>3</sup> ( $15.0$ °C / $59.0$ °F)<br>Method: Unspecified |
| Solubility(ies)                         |   |
| Water solubility                        | : negligible  |
| Solubility in other solvents            | : Data not available  |
| Partition coefficient: n-octanol/water  | : Pow: $> 6$ (based on information on similar products)                   |

# Safety Data Sheet

## Shell Spirax S6 AXME 80W-140

Version 2.3

Revision Date 10.08.2016

Print Date 11.08.2016

Auto-ignition temperature : > 320 °C / 608 °F

### Viscosity

Viscosity, dynamic : Data not available

Viscosity, kinematic : 271 mm<sup>2</sup>/s (40.0 °C / 104.0 °F)  
Method: ASTM D445

30.5 mm<sup>2</sup>/s (100 °C / 212 °F)  
Method: ASTM D445

Explosive properties : Not classified

Oxidizing properties : Data not available

Conductivity : This material is not expected to be a static accumulator.

Decomposition temperature : Data not available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

Chemical stability : Stable.

Possibility of hazardous reactions : Reacts with strong oxidising agents.

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials : Strong oxidising agents.

Hazardous decomposition products : Hazardous decomposition products are not expected to form during normal storage.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on data on the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Exposure routes : Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

#### Acute toxicity

##### Product:



# Safety Data Sheet

## Shell Spirax S6 AXME 80W-140

Version 2.3

Revision Date 10.08.2016

Print Date 11.08.2016

Acute oral toxicity : LD50 rat: > 5,000 mg/kg  
Remarks: Expected to be of low toxicity:

Acute inhalation toxicity : Remarks: Not considered to be an inhalation hazard under normal conditions of use.

Acute dermal toxicity : LD50 Rabbit: > 5,000 mg/kg  
Remarks: Expected to be of low toxicity:

### Skin corrosion/irritation

**Product:**

Remarks: Expected to be slightly irritating., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

### Serious eye damage/eye irritation

**Product:**

Remarks: Expected to be slightly irritating.

### Respiratory or skin sensitisation

**Product:**

Remarks: Not expected to be a skin sensitiser.

**Components:**

**N-phenyl-1-naphthylamine:**

Remarks: May cause an allergic skin reaction in sensitive individuals.

### Chronic toxicity

### Germ cell mutagenicity

**Product:**

: Remarks: Not considered a mutagenic hazard.

### Carcinogenicity

**Product:**

Remarks: Not expected to be carcinogenic.

| Material                 | GHS/CLP Carcinogenicity Classification |
|--------------------------|--|
| N-phenyl-1-naphthylamine | No carcinogenicity classification.     |

### Reproductive toxicity

# Safety Data Sheet

## Shell Spirax S6 AXME 80W-140

Version 2.3

Revision Date 10.08.2016

Print Date 11.08.2016

**Product:**

:  
Remarks: Not expected to impair fertility., Not expected to be a developmental toxicant.

**STOT - single exposure**

**Product:**

Remarks: Not expected to be a hazard.

**STOT - repeated exposure**

**Product:**

Remarks: Not expected to be a hazard.

**Aspiration toxicity**

**Product:**

Not considered an aspiration hazard.

**Further information**

**Product:**

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

---

**SECTION 12. ECOLOGICAL INFORMATION**

Basis for assessment : Ecotoxicological data have not been determined specifically for this product.  
Information given is based on a knowledge of the components and the ecotoxicology of similar products.  
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).

**Ecotoxicity**

**Product:**

Toxicity to fish (Acute toxicity) :

Remarks: Expected to be harmful:  
LL/EL/IL50 10-100 mg/l

# Safety Data Sheet

## Shell Spirax S6 AXME 80W-140

Version 2.3

Revision Date 10.08.2016

Print Date 11.08.2016

Toxicity to crustacean (Acute toxicity) :  
Remarks: Expected to be harmful:  
LL/EL/IL50 10-100 mg/l

Toxicity to algae/aquatic plants (Acute toxicity) :  
Remarks: Expected to be harmful:  
LL/EL/IL50 10-100 mg/l

Toxicity to fish (Chronic toxicity) :  
Remarks: Data not available

Toxicity to crustacean (Chronic toxicity) :  
Remarks: Data not available

Toxicity to microorganisms (Acute toxicity) :  
Remarks: Data not available

### **Components:**

#### **N-phenyl-1-naphthylamine :**

M-Factor : 1

### **Persistence and degradability**

#### **Product:**

Biodegradability :  
Remarks: Expected to be not readily biodegradable., Major constituents are expected to be inherently biodegradable, but contains components that may persist in the environment.

### **Bioaccumulative potential**

#### **Product:**

Bioaccumulation :  
Remarks: Contains components with the potential to bioaccumulate.

Partition coefficient: n-octanol/water :  
Pow: > 6Remarks: (based on information on similar products)

### **Mobility in soil**

#### **Product:**

Mobility :  
Remarks: Liquid under most environmental conditions., If it enters soil, it will adsorb to soil particles and will not be mobile.

Remarks: Floats on water.

### **Other adverse effects**

no data available

#### **Product:**

Additional ecological information :  
Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities., Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.  
Poorly soluble mixture., May cause physical fouling of aquatic organisms.

# Safety Data Sheet

## Shell Spirax S6 AXME 80W-140

Version 2.3

Revision Date 10.08.2016

Print Date 11.08.2016

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.  
Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be complied with.

Contaminated packaging : Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

---

### SECTION 14. TRANSPORT INFORMATION

#### National Regulations

##### ADG

Not regulated as a dangerous good

#### International Regulations

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category : Not applicable

Ship type : Not applicable

Product name : Not applicable

Special precautions : Not applicable

#### Special precautions for user

Remarks : Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

Additional Information : MARPOL Annex 1 rules apply for bulk shipments by sea.

---

### SECTION 15. REGULATORY INFORMATION

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : No poison schedule number allocated

# Safety Data Sheet

## Shell Spirax S6 AXME 80W-140

Version 2.3

Revision Date 10.08.2016

Print Date 11.08.2016

Scheduling of Medicines and  
Poisons (SUSMP)

Product classified as per Work Health Safety Regulations – Implementation of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) 2012 and SDS prepared as per national model code of practice for preparation of safety data sheet for Hazardous chemicals 2011 based on Globally Harmonized Classification version 3.

National Model Code of Practice for the Labelling of Workplace Hazardous Chemicals (2011).

Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG code).

### Other international regulations

**The components of this product are reported in the following inventories:**

EINECS : All components listed or polymer exempt.  
TSCA : All components listed.  
AICS : All components listed.

---

## SECTION 16. OTHER INFORMATION

### Full text of H-Statements

H302 Harmful if swallowed.  
H317 May cause an allergic skin reaction.  
H373 May cause damage to organs through prolonged or repeated exposure if swallowed.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox. Acute toxicity  
Aquatic Acute Acute aquatic toxicity  
Aquatic Chronic Chronic aquatic toxicity  
Skin Sens. Skin sensitisation  
STOT RE Specific target organ toxicity - repeated exposure

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

Date of preparation or review : 10.08.2016

### Further information

Other information : A vertical bar (|) in the left margin indicates an amendment from the previous version.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.